# Eaton XTCE500M22Y

# Catalog Number: XTCE500M22Y

Eaton XT IEC contactor, 500A, 48 Vac 40 Hz, 110 Vac 60 Hz, 2NO-2NC, 500A, Frame M, 160 mm, 40-60 Hz, 150, 200, 400, 500 hp (3PH @200, 230, 460, 575 V), Three-pole, Non-reversing, , Screw terminals, FVNR

## General specifications



Eaton XT IEC contactor

Product Length/Depth

Catalog Number

XTCE500M22Y

**UPC** 

782116487301

9.921 in

**Product Height** 

7.362 in

**Product Width** 

**Product Weight** 

Warranty

17.6 lb

10 in

1 year

Compliances

Certifications

**RoHS Compliant** 

**UL Listed** EN 60947

**CE Marked** 

**CSA** Certified

IEC 60947

#### **Catalog Notes**

Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Photo is representative

## Product specifications

Amperage Rating

500A

HP rating - max

150, 200, 400, 500 hp (3PH @200,230,460,575 V)

**Number Of Poles** 

Three-pole

Type

Full voltage non-reversing contactor

Frequency rating

40-60 Hz

Frame size

160 mm

**Terminals** 

Screw terminals

Coil

48 Vac, 50 Hz

Coil voltage

48 Vac 40 Hz, 110 Vac 60 Hz

Contact configuration

2 NO, 2 NC

Continuous ampere rating

500 A

Series

XT IEC

Operation

Non-reversing

#### Resources

Specifications and datasheets

Eaton Specification Sheet - XTCE500M22Y

Warranty guides

Selling Policy 25-000 - Distribution and Control Products and Services



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia